ADLINK Neuron: An industrial oriented ROS2-based platform

ROS-Industrial America Annual Meeting

HaoChih, Lin

ROS Technical Consultant Advanced Robotic Platform Group 2018.03



Building Forward Together















ADLINK Overview



ADLINK Overview

Over 20 Years of Embedded Experience



Vertical Markets & Key Customers



Industrial Automation



Test & Measurement



Medical / Healthcare



Тга



Transportation



Telecom & Networking



Military &

Aerospace

Customers Across Vertical Markets



A Revolution of Production





Massive Production








Factories of the Future (FoF)







Source: FFG / ADLINK


Building Forward Together

Autonomous Mobile Robot in FoF









ROS 2 with OpenSplice DDS



Motion

planning

Application















ROS abstract middleware layer (RMW)





Vortex OpenSplice Commercial version

Vortex OpenSplice Community version Vortex XRCE

Time Deterministic Network

(Guaranteed Latency)






ADLINK ROS-2 Industry-Grade Products



Motion, Vision, Measurement



Embedded ROS-based PC for industrial arms

ADLINK ROS-based PC for AMR


Toward Distributed, Autonomous Way!




• ROS 1 Standalone

ROS 2 coordination among machines,

adopt DDS (pub-sub)





ROS 2 removes the Master Node

- Real-time
- Powerful QoS
- Standard tech.
- Dynamic discovery)









ARM



An industrial oriented ROS2-based platform







www.worldrobotics.org. September 2016

CPU Type

Intel



CPU: i7/5/3, Celeron RAM: 4~32G (DDR4) SSD: 32G ~ (mSATA) PCle x16 gen3 * 1 PCle x1 gen2 * 1

RS232 * 3, RS485* 1, GPIO * 10, USB 3/2 * 4 (both) GbE port * 2, miniPCIe * 2, Input: 12 or 5 Volt

- OpenSplice DDS fine tuning (shared memory)
- Real-time kernel (Xenomai)
- ROS supported sensors integration/testing
- ROS 1(Kinetic) & ROS 2 (GPIO control node)



An industrial oriented ROS2-based platform

Hardware

- Replaceable CPU & Extensible RAM
- RS-232 x4 & RS-485 x2★
- PCIe x16 Gen3.0 (Nvidia GPU)★
- Two standalone USB 3.0 ports
- GPIO 10 pins & I2C, SPI★
- Kernel & Middleware
- Realtime OS (Xenomai)★
- Linux drivers maintenance (Nvidia GPU)
- GPIO integration/testing (API for users)
- PrismTech DDS fine tuning (shared memory)★
- ROS supported sensors integration/testing

Software

- Pre-configured OS image (Ubuntu)
- ROS 1(Kinetic) & ROS 2 (released)
- ROS 2 nodes for I/O control
- ROS demo scripts (VSLAM, Navigation...) *





















An industrial oriented ROS2-based platform








Cases & Demo: DDSBot





ADLINK Neuron Use Cases



Real Implementation/Cases

- Fog/Edge Computing Test-bed (ROS2/DDS for cooperative SLAM)
- AMR/AGV onboard computer
 (ROS2/DDS for multi robots collaboration)
 (Realtime implementation & robotic arm manipulator)
- Smart Grid
 (DDS node for each Electric Tower)
- Agriculture Factory
 (ROS2/DDS node for each industrial machine)





ADLINK NeuronBot



ROS 1.0/2.0 based swarm robots architecture

■ Architecture Overview



ADLINK NeuronBot



ROS 1.0/2.0 based swarm robots architecture **ROS 2.0** ■ Software Architecture (Swarm) ddsbot_manager **ROS 2.0 (OpenSplice DDS) Topics ROS 2.0 ROS 2.0 ROS 2.0** ROS 2 parameter bridge parameter bridge parameter bridge /swarm poses /swarm poses /swarm poses ROS₁ /swarm_goals /swarm_goals /swarm_goals |/swarm_poses /swarm poses I/swarm poses robot robot robot goal goal goal tf to tf to tf to id filter filter filter transfor transfor transfor filter filter filter move base move base move_base /multi_robots /multi_robots /multi_robots simple/goal simple/goal i simple/goal /tf Swarm costmap layer Swarm costmap layer Swarm costmap layer ROS 1 (Kinetic) ROS 1 (Kinetic) ROS 1 (Kinetic) **Navigation Stack Navigation Stack Navigation Stack**

::: RUS

Robot 1

Robot 2

Robot N

ADLINK NeuronBot



Demo Video in Embedded World Conference 2018

Summary



- The source codes of Vortex OpenSplice will be fully opened by March!
- Vortex OpenSplice has been successfully tested with ROS2 (shared mem)
- ADLINK Neuron will be officially released by Q2 2018
 - Offer reliable/robust ADLINK ROS2/DDS Industrial Developer Kit
 - Easy, abstract, reliable, rea-time ROS platform (DDS-based)
 - Speed up developing cycle
 - Enable ROS2 ecosystem in Asia
 - Increase ROS2 adoption for AMR/Arm/Smart factory

